

## Assembly & Operations Manual ICOS (In Cab On Seat Gun Holder) **PATENT PENDING**



### Assembly information:

- This product has an installation rating of: **Easy**
- Approximate Assembly time: **5 Minutes**



Seizmik makes Windshields, Doors, Tops, Hood Racks, Brush Guards, and other great accessories for utility vehicles & side x sides. Our products are engineered tough for long life and tested under the harshest of conditions.

Always observe the warnings and precautions in this manual when using your Seizmik products. For best results, carefully follow the instructions in this manual and make no modifications.

Seizmik products are designed, developed and manufactured by Vialink Corp. If you have any questions, comments, need assistance, or are missing parts, please call 1-866-838-3366 between 9:00AM and 5:00PM EST. You can email us at [support@seizmik.com](mailto:support@seizmik.com)

**\*Always transport guns UNLOADED and pointed in a safe direction. Seizmik is not responsible for injury to persons or damage to the weapon due to improper handling.**

## Parts List



Parts:

- A. ICOS Foam Base
- B. Seatbelt Insert
- C. Strap + buckle assembly with secure block (X2)

## Insert Straps and Seat Belt Insert into Foam Base



1. Start by Installing the plastic Seatbelt insert by placing it through the large center hole.



2. When installed, the seatbelt insert should lay flush and match the style lines of the foam base.

## Insert Straps and Seat Belt Insert into Foam Base



3. Insert the gun hold down straps as shown. Feed the male end of the buckle through the side hole and up through the middle top hole.



4. Insert the strap block into the hole. Push the block in until its flush and ensure the block is on top of the strap. (The strap should be underneath the plastic block.)

## Fasten Base with Seatbelt



5. Place the assembly on the vehicle seat. Run the seat belt through the middle hole and buckle into the seatbelts receptacle. Pull the loose tab to get the seatbelt as tight as possible.



6. Place gun into channel as pictured above. Buckle the gun hold down strap and pull tight. For best results, place the gun hold down strap in the notch on the stock (seen above).